



# ENERPOWER S.R.L.

UFFICIO E DEPOSITO 20900 MONZA (MB) Via U. Boccioni n.7

Tel. 039 833172/r.a - Fax. 039 2230441

CF e P.IVA 03172330965 N.Registro PILE IT11030P00002515

N. REA MB- 1652616 - Registro A.E.E. n. IT1007100002 CODICE UNIVOCO SUBM70N

[www.enerpowersrl.com](http://www.enerpowersrl.com)

## 2000W MPPT inverter with multi functions

### FEATURES

- \* Pure sine wave output (THD<5%)
- \* Surge power capability up to 4000w
- \* Complete LED indication for operating status
- \* Solar charging current 20A
- \* Fast transfer time 10ms
- \* 1.5 year global warranty
- \* Selectable UPS or Energy saving mode
- \* 2000W rated output
- \* High efficiency up to 90%
- \* Full digital controller
- \* AC battery charger current 15A
- \* Three stage charge ways

Model		112	124	148	212	224	248
INVERTER	RATED PPOWER	2000W					
	SURGE POWER	4000W					
	AC VOLTAGE	110V			230V		
	FREQUENCY	60+1Hz			50+1Hz		
	WAVEFORM	Pure sine wave inverter (THD<5%)					
	AC REGULATION	10%					
	BAT.VOLTAGE	12V	24V	48V	12V	24V	48V
	VOLTAGE RANGE	10.5-15V	21-30V	42-60V	10.5-15V	21-30V	42-60V
	NO LOAD CURRENT DRAW	0.84A	0.42A	0.21A	0.84A	0.42A	0.21A
EFFICIENCY	87%	88%	89%	88%	89%	90%	
AC CHARGER	CHAGER CURRENT	15A	8A	4A	15A	8A	4A
	INPUT VOLTAGE RANGE	80-130VAC			170-260VAC		
	OUTPUT VOLTAGE	12V	24V	48V	12V	24V	48V
MPPT SOLAR CHARGER	MPPT CHARGER EFFICIENCY	97%			97%		
	INPUT VOLTAGE RANGE	15-70V	24-70V	48-70V	15-70V	24-70V	48-70V
	OUTPUT VOLTAGE	12V	24V	48V	12V	24V	48V
	SOLAR CHARGER CURRENT	20A Max					
PROTECTIONS	BAT.LOW ALARM(VDC)	10. 8+0. 2	21. 6+0. 4	43. 2+0. 8	10. 8+02	21. 6+0. 4	43. 2+0. 8
	BAT.LOW SHUTDOWN	10. 2+0. 2	20. 4+0. 4	40. 8+0. 8	10. 2+02	20. 4+0. 4	40. 8+0. 8
	BAT.OVER SHUTDOWN	15. 5+0. 2	31±0. 4	62±0. 8	15. 5+0. 2	31±0. 4	62±0. 8
	BAT.REVERSE POLARITY	FUUSE					
	OUTPUT OVER LOADS	120%rated power(shut down output voltage re-power on to recovery)					
	OUTPUT OVER TEMP	75°C(Shut down output voltage.re-power on to recovery)					
	OUTPUT SHORT	shut down output voltage					
ENVIRONMEN T	WORKING TEMP	0~+40°C@100% Ioad; 60°C@50% Ioad					
	WORKING HUMIDITY	20%-90% RH non-condensing					
	SHORTAGE TEMP	- 30~70°C					
SAFETY	CERTIFICATION	EMC LVD ROHS					
OTHERS	DIMESION	410*220*150MM					
	PACKING	550*350*260MM,1PCS/CTN,9.7KGS					